




Secure Digital Scan Card

Series 3

Specification Sheet

PHYSICAL CHARACTERISTICS

	SDSC 3E Entry Level 	SDSC 3M Mid-Range 	SDSC 3P Performance 
Dimensions	61.5 x 28.0 x 14.6 mm		66.5 x 29.4 x 20.0 mm
Total Mass	8 g (0.3 oz)		17 g (0.6 oz)

ENVIRONMENTAL SPECIFICATIONS

	SDSC 3E Entry Level	SDSC 3M Mid-Range	SDSC 3P Performance
Operating Temperature	32 to 122°F (0 to 50°C)		
Storage Temperature	-22 to 158°F (-30 to 70°C)	-40 to 158°F (-40 to 70°C)	
Relative Humidity	5% to 95% non-condensing		
Ambient Light	0.5 ft. candles (5 lux) to 8,000 ft. candles (86,112 lux)		Sunlight: 10,000 ft. candles (107,640 lux) Artificial light: 450 ft. candles (4,844 lux)

ELECTRICAL SPECIFICATIONS

	SDSC 3E Entry Level	SDSC 3M Mid-Range	SDSC 3P Performance
Operating Voltage	3.3 V		
Power Consumption (3.3 V)	Standby: 4 mA (13 mW) Scanning: 64 mA (211 mW)	Standby: 4 mA (13 mW) typical Scanning: 90 mA (297 mW) typical	
Laser Power (at 650 nm)	N/A	0.7 mW (±0.1 mW)	1.7 mW (±0.2 mW)

Secure Digital Scan Card

Series 3

Specification Sheet

PERFORMANCE SPECIFICATIONS

	SDSC 3E <i>Entry Level</i>	SDSC 3M <i>Mid-Range</i>	SDSC 3P <i>Performance</i>
Scanner Type	Symbol CSE600 CMOS linear imager	Symbol SE-955 Class 1 laser	Symbol SE-955 Class 2 laser
Types of Bar Codes Decoded	Linear (1D)	Linear (1D), Stacked linear composite (RSS-14)	
Symbologies Decoded	Codabar, Code 11, Code 128, Code 39, Code 93, D 2 of 5, I 2 of 5, MSI, UPC/EAN, Webcode	Same as SDSC 5E (except Webcode) plus: Chinese 2 of 5, RSS-14/Limited/Expanded	
Scan Repetition Rate	Frame rate varies with the amount of ambient light	100 scans/sec bi-directional	
Optical Resolution	N/A	0.004 in. (0.102 mm) minimum/bar code element width (X Dimension)	
Print Contrast	35% MRD measured at 675 nm	Minimum 25% absolute dark/light reflectance (MRD) measured at 650 nm	
Scan Angle	N/A	Wide (default): 47° ±3° Narrow: 35° ±3°	
Decode Distance*	3.18 to 60.96 cm (1.25 to 24.00 inches) typical	2.50 to 88.90 cm (1.00 to 35.00 inches) typical	2.50 to 114.30 cm (1.00 to 45.00 inches) typical

HARDWARE AND SOFTWARE COMPATIBILITY

	SDSC 3E <i>Entry Level</i>	SDSC 3M <i>Mid-Range</i>	SDSC 3P <i>Performance</i>
Operating System Support	Windows Mobile 5.0 for Pocket PC/Pocket PC Phone Edition/ 6 Classic/Professional Windows Mobile 2003/2003SE with BSQUARE SDIO <i>Now!</i> software in ROM Palm OS 5.2 or greater		
Compatibility	Windows COM port		
Interface Standards	Secure Digital I/O		

INCLUDED SOFTWARE AND HARDWARE

	SDSC 3E <i>Entry Level</i>	SDSC 3M <i>Mid-Range</i>	SDSC 3P <i>Performance</i>
Included Software	Installation Utility SocketScan for Windows Mobile SocketScan for Palm OS Socket Floating Trigger for Windows Mobile		
Package Contents	Secure Digital Scan Card CD with software and user documentation		

Secure Digital Scan Card

Series 3

WARRANTY, REGULATORY COMPLIANCE

	SDSC 3E <i>Entry Level</i>	SDSC 3M <i>Mid-Range</i>	SDSC 3P <i>Performance</i>
Warranty	One year		
Certification/ Compliance	FCC: Part 15, Class B CE: EN55024:2003 C-TICK: s.182 RoHS	FCC: Part 15, Class B ICES-003 Class B AS 3548 C-TICK: s.182 21CFR1040.10	CE: EN55024:2003 CISPR 22 Japan VCCI Class B RoHS 21CFR1040.11**

SKU NUMBERS

	SDSC 3E <i>Entry Level</i>	SDSC 3M <i>Mid-Range</i>	SDSC 3P <i>Performance</i>
SKU #	IS5300-464	IS5304-732	IS5306-736



Manicon Technology Limited

Unit 12, 8/F, New City Centre, Kwun Tong,
Kowloon, Hong Kong

Tel: 2836-3162 Fax: 2836-3093

E-Mail: sales@manicon.com

Web Page: <http://www.manicon.com>