

MC9000-S Specification Highlights

Market: Route Accounting

Applications

Automated ordering, Inventory reconciliation, Delivery tracking
Full service vending, Direct Exchange/Uniform Communication Standard (DEX), Competitive surveys, Shelf space analysis, Route optimization

User

Pre-sales, Delivery, Vending, Merchandiser, Conventional route sales

Market: Field Service

Applications

Field automation
Inventory management
Logistics optimization

User

Field service technicians

Market: Public Safety

Applications

Citations and parking tickets
Real-time visibility to centralized databases

User

Law enforcement officers
Supervisors

Market: Transportation and Logistics

Applications

Pick-up and delivery
Fleet management
Vehicle tracking and maintenance
Baggage and cargo tracking

User

Route drivers
Shipping and receiving personnel
Baggage and cargo personnel

Specifications are subject to change without notice. Symbol®, Enterprise Mobility Company™ and AirBEAM® are registered trademarks of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.

Physical and Environmental Characteristics

Dimensions:	7.6 in L x 3.6 in. W x 1.7 in. H 19.3 cm L x 9.1 cm H x 4.3 cm H
Weight:	20-23 oz., configuration-dependent
Keyboard:	28-key
Display:	Embedded CE models: 3.8 in. 1/4 VGA Mono or Color Windows Mobile models: 3.8 in. 1/4 VGA Mono or Color
Power:	Removable, rechargeable 7.2 volt Lithium ion 1550 mAh, 11.1 watt hours

Performance Characteristics

CPU:	XScale PXA255 processor at 400 MHz
Operating System:	Microsoft Windows Embedded CE. NET or Windows Mobile 2003 with Pocket PC Phone Edition
Memory (RAM/ROM):	Embedded CE: 32/32 MB Windows Mobile: 64/64 MB or 128/64 MB
Application Development:	SDK available through Symbol Developer Zone Web site
Data Capture Options:	1D laser scan engine 1D and 2D imaging engine omnidirectionally reads symbologies and captures grayscale images and signatures with intuitive laser aiming

User Environment

Operating Temperature:	Monochrome: -4 F° to 122° F (-20° C to 50° C) Color: -4 F° to 122° F (-20° C to 50° C)
Storage Temperature:	-25° F to 160° F (-40° C to 70° C)
Humidity:	5% to 95% non condensing
Drop Spec:	Multiple drops to concrete: 6 ft. (1.8 m): -20° C to 50° C
Tumble:	2,000 one-meter tumbles at room temperature (4,000 drops)
Environmental Sealing:	IP64 (electronic enclosure, display and keypad)
ESD:	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge

Wireless Data Communications

WLAN:	Symbol Spectrum24, 802.11b, 802.11
Output Power:	100 mW U.S. and international
Data Rate:	802.11b: 11 MB per second DS 802.11: 2 MB per second FH
Antenna:	Internal
Frequency Range:	Country-dependent; typically 2.4 to 2.5 GHz
PAN (Bluetooth Support):	Optional
WWAN:	GSM / GPRS and CDMA (1XRTT)

Peripherals and Accessories

Cradles:	Single-slot serial/USB, vehicle, 4-slot Ethernet, 4-slot charge only
Printers:	Supports extensive line of Symbol-approved printers and cables
Charger:	Universal battery charger, 4-slot battery charger
Other Accessories:	Cable adapter module; snap-on magnetic stripe reader; modem module; holster; full set of cables; and user accessible SD card slot

Regulatory

Electrical Safety:	Certified to UL60950, CSA C22.2 No. 60950, EN60950/IEC 950
EMI/RFI Radio Versions:	North America: FCC Part 2 (SAR), FCC Part 15, RSS210 Class B, EN 301 489-1, 489-17
EMI/RFI Batch Versions:	EU: EN55022 Class B EN55024 Japan: CISPR 22, Class B Australia: AS3548 North America: FCC Part 15, ICES 003 Class B
Laser Safety:	IEC Class2/FDA Class II in accordance with IEC60825-1/EN60825-1



Manicon Technology Limited

Unit 12, 8/F, New City Centre, Kwun Tong,
Kowloon, Hong Kong

Tel: 2836-3162 Fax: 2836-3093

E-Mail: sales@manicon.com

Web Page: <http://www.manicon.com>