




**Card
Printer
Solutions**

*i*Series™

P330*i* and P330*m* Card Printers

**The Most Reliable & Expandable
Card Printer in its Class**




Ideal for:

- » Employee ID cards
- » Student and faculty ID cards
- » Access control cards
- » Personalized membership and loyalty cards
- » Gift cards
- » Visitor ID cards
- » Government Licenses

P330*m* Card Printer

Offering monochrome-only card printing, the P330*m* is the most cost effective solution for your personalization and monochrome printing applications.



The Zebra P330*i* is the latest generation of Zebra's most popular card printer, with tens of thousands of printers installed worldwide. Designed and built for demanding environments, the P330*i* delivers reliability and performance for high-volume card production. Expansion options for networking and card encoding give the P330*i* the flexibility to meet your specific requirements. Affordable and easy to use, the Zebra P330*i* is the new leader in performance card printers. For monochrome-only printing applications and personalization, choose the P330*m* for a lower cost alternative.

Innovative and Easy-to-Use

- » Easy plug and play USB or USB with Ethernet interface simplifies configuration
- » Printhead bracket opens wide for easy ribbon access
- » 16 character LCD screen for printer status and error reporting messages
- » Translucent card cover allows you to see when supplies are running low and blank cards can be added while printing

Encoding and Network Connectivity Expansion Options

- » 3 track magnetic stripe encoding (HiCo/LoCo)
- » Contact and contactless smart card encoding capabilities
- » Built-in 10/100 Ethernet for printer networking eliminates the need for third party external device, and includes networked printer management

Reliable and Flexible

- » Revolutionary angled card feeder design means fewer rejected cards*
- » Self-aligning printhead design for consistently uniform print quality

High Performance

- » Vibrant, true-to-life colors
- » High volume card throughput
- » Large capacity card feeder available

***i* Series™ Functionality**

- » Automatic color optimization and driver configuration
- » Enhanced ribbon formulation for optimal color output
- » Ribbon image counter and ribbon low notification

*Patent pending

P330i

Card Printer Product Specifications



General Specifications

- » 16-character LCD display
- » Windows® drivers for 2000 and XP (certified); Vista compatible
- » Bi-directional driver communication
- » Two year printer warranty
- » Two year (unlimited passes) printhead warranty

Printing

- » Color dye sublimation or monochrome thermal transfer printing
- » 144 cards per hour full color single-sided (YMCKO) (P330i only)
- » 5.2 seconds/card for P330m only
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Card Specifications

- » Types: PVC, PVC Composite, Adhesive backed
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card contact and contactless
- » Card thickness: 10 mil (.25mm) to 60 mil (1.524mm) (+/- 10%)
- » Card feeder capacity: 100 cards (30 mil) or 220 cards (30 mil)
- » Card output hopper capacity: 100 cards (30 mil)

Communications Interface

- » USB 1.1 (USB 2.0 compatible) cable included
- » Optional Built-in 10/100 Mbps Ethernet



Software drivers for the Zebra P330i Card Printer have been tested to ensure that they meet Microsoft® standards for Windows® compatibility. Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

www.zebracard.com



Ribbon Specifications*

- » i Series™ Printers require the use of i Series ribbons for full color printing (P330i only)
- » YMCKO: 200 & 330 cards/roll (P330i only)
- » 1/2 Panel YMC Full KO: 450 cards/roll (P330i only)
- » Kd0 and Kr0: 500 cards / roll (P330i only)
- » Overlay varnishes: Clear and Hologram: 350 cards/roll
- » Monochrome: 1500 (Black) & 1000 cards/roll
- » Monochrome colors: black, red, blue, green, silver, gold, white and scratch-off grey



*for optimum printer performance use Genuine Zebra Supplies

Mechanical

- » Width: 18.2 in (462 mm)
- » Depth: 9.4 in (239 mm)
- » Height: 10.1 in (256 mm)
- » Weight: 15.5 lbs (7.0 kg)

Electrical

- » 100 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » 4Mbit image memory standard
- » FCC Class A, CE, UL, CUL, and CCC approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Built-in 10/100 Mbps Ethernet
- » Smart card contact-ISO 7816 encoder (30 mil cards only)
- » Smart card MIFARE®/DESFire encoder (30 mil cards only)
- » Smart card contact station (30 mil cards only)
- » Magnetic encoder (30 mil cards only) 3 track HiCo/LoCo
- » High capacity feeder (220 cards)
- » Cleaning supplies

Genuine Zebra Supplies

- » Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra Supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.



Zebra Technologies Corporation



ISO 9001
REGISTERED

An ISO 9001 registered company ©2005 ZIH Corp.
Specifications listed are for base model printers with standard
features only unless otherwise noted. Specifications subject to
change without notice. All product and brand names are trademarks
of their respective companies. All rights reserved.
All Copyrights, Trade and Service Marks shown or depicted herein are
registered by their owners. No infringement is made for or implied by the
use thereof.

Part No. P330i-09/07