

Citizen CLP-9301



Main Features

- High performance printing at up to 12 inches per second
- Superior processing and large memory for fast throughput
- Parallel and Serial as standard; USB and Network options
- Peeler with internal rewinder and 300 dpi options
- Heavy duty metal case for durability and strength

Specifications

Model	CLP-9301	
Printing method	Thermal Transfer and direct thermal printing	
Resolution (approx)	304 dpi (12 dots / mm)	
Print speed	8 inches / sec. (203 mm/sec.)	
Print length	0.25 inches~40 inches (6.5mm ~ 1016mm)	
Print width (max)	4.53 inches, 115 mm	
Fonts	1 Scalable, 8 Bitmap	
Barcode	Code39, Extended Code 39, Code93, Code 128 UCC, Code 128 (Subset A, B, C), Codabar, Interleave 2 of 5, EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25	
2D Barcode	Maxicode, PDF-417	
Media sensor	Adjustable reflective and transmissive. Label gap, black mark or notched	
CPU	32 bit RISC CPU	
Memory	8MB DRAM 1MB Flash ROM	
User interface	Liquid Crystal Display (16x2), 2 LEDs	
Support graph	PCX, BMP, GDI	
Interfaces	Standard:	Parallel CentronicsR,

	Serial RS232C up to 115,000 baud High speed IEEE1284 Parallel, Optional: USB - Universal Serial Bus, Ethernet Network 10BaseT, PCMCIA Card Module
Media	Roll or fanfold media; continuous or perforated die-cut labels, tags & tickets; inside or outside wound Thickness: 0.0025~0.01inches (0.0635~0.254mm) Roll Diameter (max): 10 inch, 254 mm (internal) Core Diameter (min): 1.5 inches (38mm)
Ribbon	Wax, wax-resin or resin. Ink side out. Max 85mm outside diameter
Dimensions	W260 x D452 x H256 (mm)
Weight	16 kgs / 35 lbs
Power Supply	220 VAC±10%,50/60Hz
Safety Standards	CE,UL,CUL,FCC class A
Environmental	+5°C to +40°C (guaranteed print quality)
Options & accessories	Standard duty autocutter, Heavy duty autocutter, Peeler with internal rewinder, Real time clock, Interfaces - listed above

[Printer List](#)