

## High resolution 400 dpi printing

### CLP7401 - 400 dpi



Citizen's CLP label printers are synonymous with ease of use, performance and reliability. These are the most important design considerations when Citizen develops any barcode printer.

Our 400 dpi CLP 7401 printer continues these concepts with the ability to print on the smallest of labels suitable for PCBs or component manufacturing. With the standard high resolution media sensor, labels just 2.5mm (0.1 inches) can be produced.

Finally, users have no need to wonder whether our label printers are correctly set-up and ready to print. The LCD control panel displays easy-to-understand messages about the status of the printer.



#### Technical Specification

	CLP 7401
Technology	Thermal transfer and direct thermal
Resolution (approx)	406 dpi, 16 dots/mm
Print speed (max)	4 inches/second, 100 mm/s
Fonts TrueType download	1 Scalable, 8 Bitmap Supported as standard
Media types	Roll or fanfold media; continuous or perforated; die-cut labels, tags & tickets
Media sensing	Label gap, notch or reflective
Media sensors	High resolution fixed and adjustable
Media width (min-max)	0.75 - 4.65 inches, 19 - 118 mm
Media roll size (max)	8 inches, 200 mm (internal)
Media thickness	0.0025-0.01 inches, 0.635-0.254 mm
Print width (max, 400dpi)	4.1 inches, 104 mm
Print length (max) Label length (min)	10 inches, 254 mm 0.10 in, 2.54 mm
Ribbon type Ribbon length	Wax, wax-resin or resin type, ink out 360m or 74mm/3" outside diameter
Interfaces	
Parallel	Standard
RS232C	Standard
USB	Optional External
Ethernet	Optional External
WiFi	Optional External
Case type	Heavy duty metal
User interface	LCD, 3 buttons + 2 LEDs
User memory Flash expansion	2 Mb 4 Mb
Windows drivers Label design software	Yes, from dealer or web site Yes, from dealer
Options & accessories	Autocutter Peeler External rewinders Network interface, see above Flash memory card, see above
Size (WxDxH) Weight (approx)	260x452x256mm, 10.2x17.8x10.1" 12.5 kg, 27.5 lbs



**Manicon Technology Limited**  
Unit 12, 8/F, New City Centre, Kwun Tong,  
Kowloon, Hong Kong  
Tel: 2836-3162 Fax: 2836-3093  
E-Mail: [sales@manicon.com](mailto:sales@manicon.com)  
Web Page: <http://www.manicon.com>

*High resolution 400 dpi printing*

*Easy-to-use, easy-to-install clamshell mechanism*

*Parallel & serial standard; Network and WiFi options*

*Heavy duty metal case for durability*