



CL-S621 Bar Code/ Label Printer

The powerful CL-S621 offers unparalleled versatility in the desktop thermal printer class. Able to print in both direct thermal and thermal transfer mode the CL-S621 features a 360-meter ribbon for greater productivity and reduced down-time. Citizen's unique metal Hi-Lift™ mechanism allows easy access for loading of media and/or ribbons and the adjustable media sensor can handle a wide variety of label configurations including standard and pediatric medical wristbands. The powerful on-board 32 Bit RISC processor delivers exceptional throughput and fast first label out. The CL-S621 comes standard with internal parallel, serial, and USB interfaces. Optional Ethernet and Wifi interfaces are also available.

CITIZEN
Micro HumanTech

Leading Technology for Humanity



CL-S621 Bar Code/Label Printer

Features

- Powerful 32 Bit RISC processor
- Thermal transfer or direct thermal printing
- 360-meter ribbon
- Standard and pediatric medical wristband capable
- Metal Hi-Lift™ print mechanism
- Standard internal parallel, serial and USB interfaces
- Internal Ethernet and wireless LAN networking options
- Internal 5-inch (125mm) media capacity
- Zebra® and Datamax® emulations available
- Ships with Windows™ XP & Vista drivers
- Label-making software included
- Active Ribbon Control and Positioning System (ARCP)
- Internal power supply

Applications

- Healthcare
- Pharmacy labeling
- Postal service
- Product labeling
- Inventory control
- Asset tracking

Specifications

| | |
|------------------------|--|
| Printing Method | Thermal transfer / Direct thermal |
| Print Width | 4.1" (max) |
| Resolution | 203 dpi |
| Print Speed | 4 ips |
| Media Types | Roll or fanfold, Continuous or perforated, Die-cut labels, tags and tickets |
| Paper Width (min/max) | .077" - 4.65" |
| Paper Thickness | 0.0025" - 0.01" |
| Paper Roll Size | 5" (max) |
| Print Length (min/max) | .25" - 32" |
| Ribbon Type | Wax, wax-resin or resin |
| Ribbon Length | 1182' / 360m |
| Emulations | Standard: DPL™ (CL-S621), Optional: ZPL™ (CL-S621z) |
| Barcode Types | Linear Bar Codes: Code 11, Interleaved 2 of 5, Code 39, EAN-8, EAN-13, UPC-E, Code 93, Code 128, Industrial 2 of 5, Standard 2 of 5, ANSI CODABAR, LOGMARS, MSI, Plessey, UPC/EAN Extensions, UPC-A, POSTNET 2-Dimensional: Code 49, PDF-417, CODABLOCK, UPS Maxi Code, Micro PDF-417, Data Matrix, QR Code |
| Media Sensing | Sensors: Transmissive and reflective media sensors |
| Fonts | Standard: 11 system bit-mapped fonts including OCR-A, OCR-B, CG Triumvirate, CG Triumvirate bold and a True Type™ Rasterizer |
| Memory | DRAM: 8 MB Flash: 2 MB |
| Interface | Standard: IEEE 1284 parallel, RS232C, USB Optional: Ethernet or Wi-Fi (internal) |
| Drivers | Windows Drivers: Windows 2000/XP |
| Power | 120V, 2.4A, 60Hz |
| Weight: | 10.7 lbs |
| Dimensions (W x D x H) | 9.1" x 11.4" x 10.2" |
| Options | Cutter, label peeler |