

## TEC B-SA4TM



### Features:

- Thermal Transfer and direct thermal printing
- 203 / 300 dpi resolution
- Heavy duty metal case for durability and strength
- Easy label loading and printer operation
- Desktop printer with the performance of an industrial printer, offers high-speed printing
- Large choice of network interfaces: parallel, USB 2.0 and internal LAN as standard, with optional serial, wireless LAN and RFID interfaces (HF and UHF)
- SNMP Tools: allows the user to manage all the SNMP printers in the network through their IP address and serial number

### SPECIFICATIONS

| Mode                  | B-SA4TM-GS12                                                                                                                   | B-SA4TM-TS12           |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------|------------------------|
| Printing method       | Thermal Transfer and direct thermal printing                                                                                   |                        |
| Print lenght          | 6.5MM~1016MM                                                                                                                   |                        |
| Print width (max)     | 104 mm                                                                                                                         | 105.7 mm               |
| Print speed (max)     | 152.4 mm / sec.                                                                                                                |                        |
| Resolution (approx)   | 203 dpi (8 dots / mm)                                                                                                          | 300 dpi (12 dots / mm) |
| CPU                   | 32 bit RISC CPU                                                                                                                |                        |
| Interfaces            | Bidirectional Parallel, USB 2.0, LAN (100BASE)                                                                                 |                        |
| Fonts                 | Bitmap font (21 fonts), Outline font (4 types),<br>Price font (3 types)                                                        |                        |
| Support graph         | PCX, BMP, GDI                                                                                                                  |                        |
| Options & accessories | Cutter module, strip module, wireless LAN board,<br>RFID modules, RTC (real time clock)                                        |                        |
| Movable Media sensor  | Transparent (see through label gap) or reflective                                                                              |                        |
| User interface        | LCD display~16 x 2 rows ), 3 LEDs                                                                                              |                        |
| Barcode               | <b>1D Barcode:</b><br>Code39, Extented Code 39, Code93, Code 128 UCC,<br>Code 128(Subset A, B, C), Codabar, Interleave 2 of 5, |                        |

|                       |                                                                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
|                       | EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A,<br>E 2&5 add on, POSTNET, German POST, Matrix 25<br><br><b>2D Barcode:</b><br>Maxicode, PDF-417 |
| Memory                | 8MB DRAM, 1MB Flash ROM                                                                                                                        |
| Media                 | Thermal, PVC, PET                                                                                                                              |
| Ribbon                | Wax, wax-resin or resin type<br><br>Size: 3 inches (76mm)<br>Core: 1 inches (25mm)<br>Length: 450m                                             |
| Dimensions            | 238 (W) x 331.5 (H) x 401.7 (L) mm                                                                                                             |
| Weight                | 17.0 KGS (without media & ribbon)                                                                                                              |
| Power Supply          | 220 VAC±10%, 50/60Hz                                                                                                                           |
| Safety Standards      | CE, UL, CUL, FCC class A                                                                                                                       |
| Working Environmental | 40°F~100°F~4°C~38°C)<br>10~90% non condensing                                                                                                  |

[Printer List](#)