

KU-007 Plus Universal Programmable Keyboard



The TSC™ KU-007 Plus Programmable Keyboard is the easiest way to build a stand-alone printing system and works as a small portable PC to save valuable working space. The KU-007 Plus offers the unique capability of communicating with virtually every brand of bar code printer on the market today.

The KU-007 Plus Programmable Keyboard allows users to upload or download files as well as connect an input device such as a CCD Scanner to its additional RS232 interface. Simply generate desired label formats through an easy to use BASIC-like language interpreter. By downloading into the flash memory of the keyboard, you can build a stand-alone printing system instantly.

The KU-007 Plus features include:

- 2MB flash memory and 256 SRAM memory
- LCD display panel (graphic type)
- Built-in BASIC-like language interpreter
- Real-time-clock
- Password locking for security
- Built in EURO currency logo
- 6-digit floating-point calculatio

The KU-007 Plus can be applied to many applications including retail, transportation, distribution, and manufacturing environments.



Manicon Technology Limited
Unit 12, 8/F, New City Centre, Kwun Tong,
Kowloon, Hong Kong
Tel: 2836-3162 Fax: 2836-3093
E-Mail: sales@manicon.com
Web Page: <http://www.manicon.com>

Keyboard

- 68 keys

LCD display

- Graphics type

Serial interface

- COM1: 9 pins, Baud Rate adjustable from 2400 to 19200 bps, male Dsub with cable
- COM2: 9 pins, Baud Rate adjustable, from 2400 to 19200 bps, female Dsub

Dimensions

- Width: 261 mm (10.2")
- Height: 31 mm (1.2")
- Depth: 142 mm (5.6")

Memory

- 2 MB Flash memory
- 256 KB SRAM memory

Firmware

- Built-in BASIC-Like Language

KU-007 Plus features include

- Programmable and able to communicate with virtually every brand of bar code printer on the market today
- 2MB Flash Memory and 256 KB SRAM memory
- LCD display panel (graphic type)
- BASIC-Like language interpreter
- Real-time-clock
- Password locking for security
- Built-in Euro currency logo
- 6-digit floating point calculation

