

A "PLUS" VERSION OF A MOST DURABLE AND POWERFUL DESKTOP LABEL PRINTER!

TSCTM
Connecting Your Thermal Printing Needs.™



TTP-245 PLUS . TTP-343 PLUS DESKTOP THERMAL TRANSFER BAR CODE PRINTER

TSC is proud to introduce a "Plus" version of its best-selling line of printers, the TTP-245 Plus series. With enhanced electronics, TSC TTP-245 Plus series offers standard memory of 2 MB FLASH, 8 MB SDRAM and a slot for SD card that users can inexpensively expand FLASH storage up to 4 GB. The printer is equipped with a 32 bit microprocessor for fast label processing and throughput, at print speed up to 5 ips with 203 dpi resolution and 3 ips with 300 dpi version.

TTP-245 Plus series features serial, parallel and USB 2.0 communication ports standard, and offers an on-board, lesser-cost internal Ethernet LAN interface option for network installation. The user-friendly clamshell design with double-walled construction makes TTP-245 Plus series easy-to-use and the strongest thermal transfer mechanism in the industry.

Its innovative Dual-Motor gear driven design provides enough horsepower to handle 300 meter long ribbons and up to 8.4" OD rolls of labels. Two motors instead of one generate lower torque, more durability and quiet operation. The ribbon capacity of 300 meter is more than three times longer than industry standard for desktop printers.

TSC now ships TSPL-EZ™ firmware in TTP-245 Plus series. TSPL-EZ™ offers unparalleled ease of use by supporting three different printer languages out of the box including TSC printer language, TPLE (Translation Printer Language Eltron®) and TPLZ (Translation Printer Language Zebra®). TSPL-EZ™ also features internal scalable True Type fonts using the Monotype® font engine and offers powerful programming tools for integration into many applications. All TSPL-EZ™ printers are supported by Windows drivers developed by Seagull Scientific.



Value • Performance • Support

TTP-245 PLUS . TTP-343 PLUS

DESKTOP THERMAL TRANSFER BAR CODE PRINTER



SPECIFICATIONS

Printer Model	TTP-245 Plus 203 DPI	TTP-343 Plus 300 DPI
Thermal Transfer & Direct Thermal		
Print speed	2, 3, 4, 5 ips 2, 3 ips selectable with peel function	2, 3 ips selectable
Max. print width	108 mm (4.25")	104 mm (4.09")
Max. print length	2,286 mm (90")	1,016 mm (40")
Enclosure	Double-walled plastic	
Physical dimension	314mm (L) x 213mm (W) x 188mm (H) 12.36" (L) x 8.39" (W) x 7.40" (H)	
Label roll capacity	127 mm (5") OD	
Processor	32-bit RISC CPU	
Memory	<ul style="list-style-type: none"> ● 2 MB FLASH memory ● 8 MB DRAM ● SD card slot for memory expansion 	
Interface	<ul style="list-style-type: none"> ● RS-232 (max. 115,200 bps) ● Centronics ● USB 2.0 (full speed mode) 	
Power	AC Input: 100-240V universal switching power supply DC output: 24V 3.75A (external adaptor)	
Operation switch, button	One power switch & feed button	
Sensors	<ul style="list-style-type: none"> ● Gap transmissive sensor ● Moveable black mark reflective sensor ● Head open sensor ● Ribbon end sensor 	
Internal font	<ul style="list-style-type: none"> ● 8 alpha-numeric bitmap fonts ● One Monotype® Imaging CG Triumvirate Bold Condensed scalable font 	
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, China Post	
2D bar code	PDF-417, Maxicode, DataMatrix, QR Code	
Font & barcode rotation	0, 90, 180, 270 degrees	
Printer language	TSPL-EZ™	
Media type	Continuous, die-cut, black mark, fan-fold, notch	
Media wound type	Outside wound	
Media width	20~112 mm (0.78" ~ 4.4")	
Media thickness	0.06~0.19 mm (2.3 ~ 7.4 mil), max. 150g/m²	
Media core diameter	25.4~76.2 mm (1"~3")	
Label length	10~2,286 mm (0.39"~90")	
Environment condition	Operation: 5~40°C (41~104°F), 25~85% non-condensing Storage: -40~60°C (-40~140°F), 10~90% non-condensing	
Safety regulation	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/GS, CCC	
Accessories	<ul style="list-style-type: none"> ● BarTender UltraLite CD disk ● Quick start guide ● USB cable ● External universal switching power supply ● Power cord ● Label spindle, fixing tab x 2, 1.5" core adapter x 2 ● Ribbon spindle x 2 ● Ribbon rewind spindle paper core 	
Limited warranty	<ul style="list-style-type: none"> ● Printer: 1 years ● TPH: 3 months ● Platen: 50 Km 	
Factory option	<ul style="list-style-type: none"> ● Real time clock ● Main board integrated with internal Ethernet ● Peel off module assembly ● Guillotine cutter 	
Dealer option	<ul style="list-style-type: none"> ● Full cut: Paper thickness: 0.06~0.19mm, 500,000 cuts ● Partial cut: Paper thickness: 0.06~0.12mm, 500,000 cuts ● Paper thickness: 0.19 mm, 200,000 cuts ● Internal Ethernet print server module ● Keyboard display unit (KU-007 Plus and KP-200) ● External Ethernet print server ● External wireless (802.11b/g) print server ● External roll mount, media OD. 214 mm (8.4") with 1" or 3" core ● 3" core label spindle ● Contact CCD bar code scanner ● Long range linear image bar code scanner ● Laser bar code scanner 	
User option		



Manicon Technology Limited
 Unit 12, 8/F, New City Centre, Kwun Tong,
 Kowloon, Hong Kong
 Tel: 2836-3162 Fax: 2836-3093
 E-Mail: sales@manicon.com
 Web Page: <http://www.manicon.com>