

EC Thermal Receipt Printer



EC-PM-X30

Features

- 58mm/80mm/82.5mm paper width available
- IAP function supports firmware update within 5S
- Emulation Driver ESC/POS Windows/ JPOS/Linux/ Android/Mac
- Metallic frame mechanism

Specifications

Print method
Print width
Print speed
Paper thickness
Interface
Column capacity

Direct thermal
79.5±0.5mm
300mm/s
0.06~0.08mm
USB+ Lan
576 dots/line(adjustable by command)

Character size

ANK, Font A: 1.5 x 3.0mm (12x2 4 dots) Font B: 1.1x2.1mm(9x17 dots)
Chinese, traditional Chinese :3.0 x 3.0mm(2 4 x2 4 dots)

Bar code

UPC-A/UPC-E/ JAN13(EAN13)/ JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
QR CODE 、 PDF417

Code page

PC34 7(Standard Europe)/ Katakana/ PC850(Multilingual) / PC860(Portuguese) /
PC863(Canadian-French) / PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/
Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII /Latvian/ Arabic/ PT151(1251)

Auto Cutter
Cutter life
Print head life
Input buffer
NV Flash

Partial
2 million cuts
150KM
2048 Kbytes
256 Kbytes

Power adaptor
Power source
Cash drawer output
Work environment
Storage environment

AC220V, 50~60Hz
DC 24V/2.5A
DC 24V/1A
Temperature: 0~45%, Humidity: 10~80%
Temperature: -10~60%, Humidity: 10~90%

Weight
Dimension (DxWxH)

1.115 kg
133x126x130mm(WxDxH)

