

TM-T88IV

Thermal Printer

EPSON
EXCEED YOUR VISION



High-speed Thermal Printer

- Fully compatible with the TM-T88III
- Fast and versatile printing
- Easy operation
- High reliability
- Compact design



EASY OPERATION

Drop-in paper loading and standard autocutter provide easy user operation.

FAST AND VERSATILE PRINTING

The TM-T88IV prints receipt at speeds of up to 200 mm per second for both text and graphics - 30% faster than the TM-T88III. With two-color*, advanced graphic and barcode (PDF417 and QR code) printing capability, this printer provides highly customized receipts including logos and promotional messages. Its flexible page mode gives you a choice of receipt layouts.

APPEARANCE



OPTIONS



- PS-180
 - Power Supply Unit
- WH-10
 - Wall Hanging Bracket

HIGH RELIABILITY

With an MCBF of 52 million lines of receipt printing, the TM-T88IV delivers outstanding reliability that is rugged enough for the high-volume environments.



COMPACT DESIGN

The TM-T88IV has a small footprint that allows for flexible placement on your counter or wall using an optional wall-hanging bracket, freeing up valuable counter space. Furthermore, the TM-T88IV offers an improved paper cover design for increased spill resistance. Two case colors (Epson Cool White or Epson Dark Gray) are available to suit your needs.

SPECIFICATIONS

Print method	Thermal line printing	
Print Font	9 x 17 / 12 x 24	
Column capacity	56 / 42 columns	
Character size	0.99 (W) x 2.4 (H) / 1.41 (W) x 3.39 (H) mm	
Character set	95 Alphanumeric, 37 International, 128 x 11 Graphic Traditional / Simplified Chinese, Japanese, Korean	
Bar code	UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), CODE39, CODE93, CODE128, ITF, CODABAR	
Two-dimensional code	PDF417, QRCode	
Characters per inch	20.0 cpi / 15.0 cpi	
Interfaces	RS-232, Bi-directional parallel Dealer option: RS-485, USB, 10 Base-T I/F	
Data buffer	4 KB or 45 bytes	
Print speed	Max. 200 mm / sec.	
Paper	Dimensions	Roll paper: 79.5 ± 0.5 (W) x dia. 83.0 mm
	Thickness	0.06 to 0.07 mm
Power	24 VDC ± 7%	
Power consumption	Approx. 1.8 A (mean)	
D.K.D.function	2 drivers	
Reliability	MTBF	360,000 hours
	MCBF	52,000,000 lines
Overall dimensions	145 (W) x 195 (D) x 148 (H) mm	
Mass	Approx. 1.8 kg	
EMC standards	FCC, VCCI class A CE marking, AS / NZS CISPR22 class B	
Power supply (option)	PS-180	
Option	Wall-hanging bracket WH-10	
Safety standards	UL / CSA / EN	

All Features and specifications described are subject to change without notice.

EPSON and ESC/POS are registered trademarks of SEIKO EPSON Corporation.

Windows and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries.

Company and product names trademarks or registered trademarks of their respective companies.

For details, please contact:

EPSON
EXCEED YOUR VISION