

PM-80 Super High Speed Thermal Printer

Date: 26th May,2016

Specification			
Print	Model No.	PM- 80	
	Color	Black	
	Printing method	Direct Thermal	
	Printing speed	200mm/sec	
	Resolution	576dots/line or 512dots/line	
	Effective Printing Width	72mm	
Character	Character size	ANK,FontA:12×24dots, FontB:9×17dots Simplified,traditional :24×24dots	
	Character set	user option	
Paper Spec	Paper width	79.5±0.5mm	
	Paper thickness	0.06 - 0.08mm	
	Roll paper	79.5±0.5mm×φ80mm	
Buffer	Input buffer	64k bytes	
	NV flash buffer	256k bytes	
Power supply	Cash drawer control	DC 24V/1A	
	Power supply	Input: AC 110V/220V,50~60Hz	
	Power adapter	Output: DC 24V/2.5A	
Physical	Gross Weight	1.1kg	
	Dimension	195×140×142.5mm	
Auto cutter	partial		
MCBF(life)	Printing head life: 100km / Auto Cutter life: 1 million cuts		
Drivers	Win 9X/Win ME/ Win 2000/Win 2003/Win NT/Win XP/Win Vista/Windows 7 /Windows 8/Linux		
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / ITF/CODABAR/CODE39/CODE93/CODE128		
Storage environment	temperature (-10~60℃) humidity(10~90%)		
Working environment	temperature (0~45℃) humidity(10~80%)		
Command	ESC/POS		
Interface	Lan or USB+Serial		
Warranty	One Year Warranty		