

# 80mm Kiosk Printer SK1 Series



311  
Mini




- Fully opening paper cover
- Max 250mm/sec high speed printing
- Support label printing
- Sensor : Paper Empty, Paper Near-End, Black Mark & Label Gap
- Support 58/60/80/83mm paper width
- Paper core diameter 12/25.4mm changable
- Paper thickness from 59 to 150g
- Up to Φ120mm paper roll diameter
- Dual interface : USB + COM
- Compact and light weight
- Made in Japan

## Optional Accessories

Bezel



LED Bezel



Presenter



Large Paper Holder



## SPECIFICATION

### Model

### Printing Method

### Emulation

### Resolution

### Number of dots

### Printing / paper width

### Paper Thickness

### Printing Speed

### Interface

### Font

### Barcode

### 2D Barcode

### Cutter

### Sensor

### Power Supply

### Reliability

### Dimensions (WxDXH,mm)

### Weight (g)

### Safety Standard

### SK1-311 series

### SK1-V311 series

Direct line Thermal

StarPRNT™

8 dots/mm (203dpi)

432/448/576/640 dots

54/58mm, 56/60mm, 72/80mm, 80/83mm

59 ~ 150μm (W/O Presenter)

Max 250mm/sec

USB2.0 + RS232C (max. 115,200 bps)

8x16, 12X24 dots

JAN8/13, Code39/128, ITF, Codabar, UPC-A/E

QR, Maxicode, PDF417, DataMatrix

Partial or Full Cut (Command Control)

Paper Empty, Paper Near End, Black Mark, Label Gap

PS60A : 24VDC ± 5% /TYP 3A

Print Head : 150KM; Cutter: 2.0M Cut

127X145.5X85.4

127X85.4X182.3

630

725

CE, FCC, VCCI