

SPECIFICATIONS

1500 series scanner

Fast and reliable



	Linear Imager		Laser		2D Imager		
Category	Corded	1500, 1500WA	1502		1504		
	Bluetooth cordless	1560	1562		1564		
RF Communication of Bluetooth scanner	Module	Bluetooth Class 2 (2.4 GHz) Version 2.0					
	Coverage	90 m' / 295 ft. line of sight					
	Standard profile	SPP, HID					
	Optical sensor	2500 pixels	Laser		752 x 480 pixels		
Performance	Light source	Red LED 625 nm (1560: Red LED 618-626 nm)	Visable laser diode at 650 ± 15 nm		625 ±5 nm LEDs (2x)		
	Resolution	3 mil	4 mil		3 mil - 1D barcode / 5 mil - 2D barcode		
	Depth of field 13 mil barcode	0.5 to 35 cm / 0.2 to 13.8 in. (1500WA: long barcode 8.2 cm, 8 mil- 7.5 to 14.5cm / 3 to 5.7 in.)	2 to 57 cm / 0.8 to 22.4 in.		Code 39 3 mil: 6.9 to 10.7 cm / 2.7 to 4.2 in. Code 39 5 mil: 3.6 to 18.5 cm / 1.4 to 7.3 in. Code 39 7.5 mil: 0 to 25.1 cm / 0 to 9.9 in. UPCA 13 mil: 4 to 30.5 cm / 1.6 to 12 in. Code 39 20mil: 0 to 50 cm / 0 to 19.7 in. PDF417 5 mil: 2.8 to 4.5 cm / 1.1 to 1.8 in. PDF417 6.67 mil: 4.8 to 17.5 cm / 1.9 to 6.9 in. PDF417 10 mil: 0 to 22.9 cm / 0 to 9 in. PDF417 15 mil: 0 to 29.7 cm / 0 to 11.7 in.		
	Scanning angle	Pitch ± 70° Skew ± 70°	Pitch ± 65° Skew ± 50°		Pitch ±60° Skew±60°		
	PCS	Minimum 30%	Minimum 45%				
	Scan rate	200 scans, decodes / second (1500WA: 100 scans / second)	100 scans / second		60 frames / second		
	Ambient illumination	100,000 lux					
	Hands-free scanning	Auto-sense and continuous modes	Continuous mode		Auto-sense mode, continuous mode and presentation mode		
	Barcodes support	Codabar, Code 39, Code 93, Code 128,GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, MSI, Plessey, Telepen, UPC-A,UPC-E, EAN-8, EAN-13, GS1-128 (EAN-128)				1D: All major codes ² 2D: PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX)	
	Programmable features	Data editing, interface selection, symbology configuration					
	Language support	US and UK English, French, Italian, Belgian, Norwegian/Swedish, Spanish, Portuguese, German, Japanese and Turkish					
	Physical	Dimension L x W x H	15.3 x 6.1 x 9.3 cm / 6.0 x 2.4 x 3.7 in.				
		Weight without cable / with battery	145 g / 5.1 oz. (1560: 173 g / 6.1 oz.)	1502: 149 g / 5.2 oz. 1562: 177 g / 6.2 oz.		1504: 154 g / 5.4 oz. 1564: 185 g / 6.5 oz.	
Color		Black					
Switch		Tactile Switch					
Electrical	Memory for Bluetooth scanner reserver buffer / batch mode	4 K / 512 K			10 K / 4 M		
	Working hours for Bluetooth scanner	24 / 12 hours depending on the CCD Sensor mode setting (Always Active function disabled/ Always Active function enabled, default setting)	24 hours based on 1 scans / 5 seconds		16 hours based on 1 scans / 5 seconds		
	Voltage	+5 V ±10% / 3.7 V 800 mAh Li-ion battery					
	Power consumption ³ Standby / Operating	50 mA / 265 mA (1560: 45 mA / 270 mA)	1502: 35 mA / 210 mA 1562: 25 mA / 210 mA		1504: 30 mA / 280 mA 1564: 35 mA / 230 mA		
User Environment	Temperature	Operating: 0°C to 50°C / 32°F to 122°F Storage: -20°C to 60°C / -4°F to 140°F					
	Humidity	Operating: 10% to 90% Storage: 5% to 95%					
	Impact resistance	1.5 m (4.9 ft) multiple drops onto concrete (1560: 1.2 m (3.9 ft) multiple drops onto concrete)	1.2 m (3.9 ft) multiple drops onto concrete				
	Ingress protection	IP30					
	Electrostatic discharge	±8 kV contact ±15 kV air					
	EMC regulation	1500: BSMI, CE, C-tick, FCC, IC, KC 1500WA: CE, C-tick, FCC, IC 1560: BSMI, CE, C-tick, FCC, IC, KC, NCC, SRMC, TELEC	1502: CE, C-tick, FCC, IC 1562: BSMI, CE, C-tick, FCC, IC, KC, NCC, SRMC, TELEC		1504: BSMI, CE, C-tick, FCC, IC, KC 1564: BSMI, CE, C-tick, FCC, IC, NCC, KC, SRMC, TELEC		
Configuration		Setup options include Windows-based ScanMaster software, by direct connection or printing out barcode settings					
Accessories		USB, RS232 and keyboard wedge cables, Three-way desk/wall/auto-sense stand with optional weighted base, communcuation stand for Bluetooth scanner provides Bluetooth communication for up to 7 scanners, single battery charger for Bluetooth scanner					
Warranty		5 years (1560: 3 years)		3 years (engine 1 year)			

¹ It is based on communication stand without weighted base. ² All of the barcodes that 1500 series 1D scanners can read except French Pharmacode, Plessey, and Telepen. ³ The data is tested with USB interface.

© 2011 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.