



Compact Flash™
Wireless LAN Card
IEEE802.11b
Compliant



AC Adaptor



USB Cable



Vinyl Case



Access Point (Option)

Feature

- Combining PDA, Wireless Communication, and Barcode Scanning Function in one unit
- Time Saving, Real-Time Data Transmission
- Various Services, Multi-Functional, High-Tech Digital Product
- Applications: Logistics, Integration, Inventory Management, Courier Services, Hospitality, Retail, Healthcare, etc.
- 1 Year Warranty
- Battery Life: Lasting for 13-15 Hours at 1 Scan Every 5 Seconds



Manicon Technology Limited

Unit 12, 8/F, New City Centre, Kwun Tong,
Kowloon, Hong Kong

Tel: 2836-3162 Fax: 2836-3093

E-Mail: sales@manicon.com

Web Page: <http://www.manicon.com>

Mobile Computer

IQ-3000



Specifications

Processor:	ARM 7205 72MHz, 32 bits RISC CPU core.
Operating System:	Microsoft Windows CE3.0
Memory:	-16/32 MB Nand Flash+128 KB Boot ROM -32 MB SDRAM
Display:	-Screen type: 16 gray scale mono LCD with EL backlight -Screen pitch: 0.248mm dot pitch -Resolution: 240x320 pixels
Audio:	-One microphone for mono recording. -One speaker for mono playback -One 3.5mm DIA earphone jack for stereo audio output
Input Devices:	Touch Screen, Software Keyboard and Barcode scanner

Barcode Reader

Light Source:	650±10nm Visible Laser diode
Scan Rate:	100±20 scan/sec
Contrast:	0.45 minimum
Resolution:	5 mil

Symbologies

Code 39, Code 39 extended, Interleaved 2 of 5, WPC code (EAN13, EAN8, UPC-A, UPC-E), Code 128, Code 93, Coda bar, Chinese Postage Code IATA, MAI/ PLESSY, Code 32, STD 2 of 5, Code 11, EAN-128, Martix 2 of 5

Electrical:

Power consumption:	Stand by - 40 mA Suspend - 500 mA
--------------------	--------------------------------------

Communication

Infrared Port:	One IrDA 1.0 compliant SIR port. Support 115.2K bps and 30-40 cm distance
Expansion Slot:	One Compact Flash (CF) Type II
USB Port:	-One USB 1.0 compliant Device USB port. -One 1.5M cable with USB connector -File Transfer: Supports Active Sync [®]

Power System

Battery Type:	4.2 V, 1500 mAh Li-Polymer battery pack Built-in Lithium-battery charger
Battery Life:	13~15 hours at 1 scan every 5 seconds
DC jack	One
AC Adapter	Input: 100~240V AC, 50/60 Hz, Output: 5V DC, 2A

Mechanical and Environment

Dimensions:	135 (L) x 82 (W) x 18 (H) mm
Weight:	190g
Temperature:	Operation Temperature: 0°C~50°C Storage Temperature: -20°C~70°C
Relative Humidity:	5% ~ 95% (non-condensing)

Option

1. Access Point-Compliant with IEEE802.11b
2. Car Adaptor
3. KeyPad

Dealer/Distributor



Manicon Technology Limited

Unit 12, 8/F, New City Centre, Kwun Tong,
Kowloon, Hong Kong
Tel: 2836-3162 Fax: 2836-3093
E-Mail: sales@manicon.com
Web Page: <http://www.manicon.com>

*Specifications subject to change without notice